



NOTES:

1. Sections Symmetrical about  $\mathcal{C}$ .
2. Concrete Backing to be Used Where Shown or Specified.

D	VIT. CLAY PIPE		CONCRETE PIPE		F	CONCRETE BACKING CU.YD. PER LIN. FT.		REPAVING PAY LIMITS SQ.YD. PER LIN. FT.
	d min.	b	d min.	b		V.C. PIPE	CONC. PIPE	
(1)	(2)	(3)	(4)	(5)	(6)	(7)	(8)	(9)
6"	5/8"	11-3/8"	3/4"	11-1/4"	30"	.023	.023	.500
8"	3/4"	10-1/4"	7/8"	10-1/8"	30"	.028	.028	.500
10"	7/8"	9-1/8"	1"	9"	30"	.031	.032	.500
12"	1"	9"	1-3/8"	8-5/8"	32"	.038	.039	.519
15"	1-1/4"	9-1/4"	1-5/8"	8-7/8"	36"	.050	.051	.556
18"	1-1/2"	9-1/2"	2"	9"	40"	.064	.064	.593
21"	2-1/4"	9-1/4"	2-3/4"	8-3/4"	44"	.079	.079	.630
24"	2-1/2"	9-1/2"	3"	9"	48"	.094	.094	.667
27"	2-3/4"	9-3/4"	3-1/4"	9-1/4"	52"	.111	.111	.704

STANDARD DIMENSIONS  
FOR  
RIGID PIPE SEWER

CITY OF  
REYNOLDSBURG, OHIO

STANDARD  
CONSTRUCTION DRAWING

Rev.	Date	Dwg. No.
04-09-07	10-09-61	R-1